



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
[www.uspto.gov](http://www.uspto.gov)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/833,868	04/12/2001	Jori Arrakoski	NC30307	5180
32294 7590 11/03/2008 SQUIRE, SANDERS & DEMPSEY L.L.P. 8000 TOWERS CRESCENT DRIVE 14TH FLOOR VIENNA, VA 22182-6212				
EXAMINER				
WILSON, ROBERT W				
ART UNIT		PAPER NUMBER		
2419				
MAIL DATE		DELIVERY MODE		
11/03/2008		PAPER		

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

# Office Action Summary

**Application No.**

09/833,868

**Applicant(s)**

ARRAKOSKI ET AL.

**Examiner**

ROBERT W. WILSON

**Art Unit**

2419

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 14 August 2008.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1, 3-17 and 20-33 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1, 3-17, & 20-33 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO/SB/C2)  
Paper No(s)/Mail Date \_\_\_\_\_
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

***Claim Rejections - 35 USC § 103***

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1, 3-4, 5-6, 8-9, 11-13, 15-17, 20-24, 26-30, & 32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Haas (U.S. Patent No.: 6,304,556) in view of Liu (U.S. Patent No.: 6,980,537)

Referring to claim 1, Haas teaches: a system (Fig 3) comprising: a first-tier mesh formed of a plurality of first tier nodes (28 or first tier has a plurality of nodes per Fig 3) each of the first-tier nodes of the plurality of first tier nodes configured to communicate data within the first tier with at least selected other of the first-tier nodes (routing provided as peer to peer per col. 8 line 37 to col. 9 line 17) at least one of the first tier nodes forming a sink node (CH 3 per Fig 3 or sink node)

At least a second-tier mesh formed of a plurality of second tier nodes each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected other of the second-tier nodes (CH1-CH4 in 32 per Fig 3 are second tier nodes in a mesh which are capable of communicating)

a second-tier sink node further capable of communicating with the first-tier sink node of said first-tier sink mesh (CH3 in 32 or second tier-sink node is capable of communicating with CH3 in 28 or first tier sink node per Fig 3)

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Art Unit: 2419

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

In addition Haas teaches:

Regarding claim 21, wherein at least one tier-node and said first-tier mesh and at least one second tier node of said second tier mesh are not collocated the at least one first-tier node located distance from the at least one second tier node located distant from the at least one second tier node configured to communicate with the at least selected other of the first-tier nodes and the at least one second-tier node located distant from the at least one first-tier node capable of communicating with the at least selected other of the second tier node (The Ad hoc network of Fig 3 is not co-located)

Referring to claim 5, Haas teaches: a system (Fig 3) comprising: a first-tier mesh formed of a plurality of first tier nodes each of the first-tier nodes of the plurality of first tier nodes configured to communicate data within the first tier with at least one other of the first-tier nodes (28 or first tier mesh has a plurality of nodes capable of communicating per Fig 3)

At least a second-tier mesh formed of a plurality of second tier nodes each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected other of the second-tier nodes (CH1-4 in 32 per Fig 3 are second tier nodes capable of communicating) at least one of the second-tier nodes forming a second-tier sink node (Each of nodes CH1-4 in Fig 32 are sink nodes) the second-tier sink node further capable of communicating with the first-tier sink node of said first-tier sink mesh (Each of the Sink nodes CH1-CH4 in 32 are capable of communicating with their counterpart sink node CH1 to CH4 respectively per Fig 3)

Wherein the first-tier mesh comprises an ad-hoc mesh which exhibits an ad-hoc configuration and an ad-hoc number of first-tier nodes (first tier per Fig 3 is ad-hoc per col. 8 line 39 which inherently contains an ad-hoc number of first tier nodes) and

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 8, Haas teaches: a system (Fig 3) comprising: a first-tier mesh formed of a plurality of first tier nodes (28 or first tier has a plurality of nodes per Fig 3) each of the first-tier nodes of the plurality of first tier nodes configured to communicate data within the first tier with at least selected other of the first-tier nodes (routing provided as peer to peer per col. 8 line 37 to col. 9 line 17) at least one of the first tier nodes forming a sink node (CH 3 per Fig 3 or sink node)

At least one of the second-tier nodes forming a second-tier sink node (CH1-CH4 in 32 per Fig 3 are second tier nodes) which are configured to communicate with the first-tier sink node of the first-tier mesh (CH1-CH4 in 32 per Fig 3 are second tier nodes in a mesh which are capable of communicating with their respective first tier counter part)

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: wherein said second tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes or first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: wherein said second tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes (col. 14 lines 27 to 61) and first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes and first tier mesh operational characteristic and second tier operation characteristics being

dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 9, the combination of Haas and Liu teach the system of claim 8,

Haas does not expressly call for: wherein the second-tier nodes are stationary.

Liu teaches wherein the second-tier nodes are stationary (Fig 8)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add the second-tier nodes are stationary of Liu in place of the ad hoc nodes of the combination of Haas and Liu in order to build a network which can utilize terrestrial interconnections and increase the bandwidth between second tier nodes.

Referring to claim 11, Haas teaches: a system (Fig 3) comprising: a first-tier mesh formed of a plurality of first tier nodes (28 or first tier has a plurality of nodes per Fig 3) each of the first-tier nodes of the plurality of first tier nodes configured to communicate data within the first tier with at least selected other of the first-tier nodes (routing provided as peer to peer per col. 8 line 37 to col. 9 line 17) at least one of the first tier nodes forming a first-tier sink node (CH 3 per Fig 3 or sink node)

At least a second-tier mesh formed of a plurality of second tier nodes each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected other of the second-tier nodes (CH1-CH4 in 32 per Fig 3 are second tier nodes in a mesh which are capable of communicating) the second-tier sink node further capable of communicating with the first-tier sink node of said first-tier sink mesh (CH3 in 32 or second tier-sink node is capable of communicating with CH3 in 28 or first tier sink node per Fig 3)

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: a third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes capable of communicating data with at least selected other of the third tier nodes, at least one of the third-tier nodes forming a third tier sink node and first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: a third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes capable of communicating data with at least selected other of the third tier nodes (col. 5 lines 39 to 53 and per col. 14 lines 29 to 61 and per Fig 8) at least one of the third-tier nodes forming a third tier sink node (super node is a third tier sink node col. 5 lines 39 to 53 and per col. 14 lines 29 to 61 and per Fig 8) and first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes capable of communicating data with at least selected other of the third tier nodes, at least one of the third-tier nodes forming a third tier sink node and first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 12, the combination of Haas and Liu teach: the system of claim 11 and the first tier nodes of said first-tier mesh are operable pursuant to a first tier mesh operational characteristics where the second tier nodes of said second-tier mesh are operational pursuant to second-tier operational characteristics and Haas teaches a third tier (multiple tier)

Haas does expressly call for: third-tier operational characteristics, respectively, being at least in some part dissimilar (different operational characteristics for each tier per col. 6 lines 41 to 63)

It would have been obvious to add the different operation characteristic of each tier of Liu to the three tiered network of the combination of Liu and Haas in order to insure that the communication between each tier does not interfere.

Referring to claim 13, the combination of Haas and Liu teach: the system of claim 11.

Haas does not expressly call for: wherein said third-tier mesh comprises a point-to-point mesh which exhibits a fixed configuration and fixed number of third tier nodes

Liu teaches: wherein said third-tier mesh comprises a point-to-point mesh which exhibits a fixed configuration and fixed number of third tier nodes (Fig 8)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add the third-tier mesh comprises a point-to-point mesh which exhibits a fixed configuration and fixed number of third tier nodes of Liu in place of the third tier nodes of the combination of Haas and Liu in order to utilize a terrestrial backbone which provides for additional bandwidth to be utilized between nodes.

Referring to claim 15, Haas teaches: a system (Fig 3) comprising:

Art Unit: 2419

a first-tier mesh formed of a plurality of first tier nodes (28 or first tier has a plurality of nodes per Fig 3) each of the first-tier nodes of the plurality of first tier nodes configured to communicate data within the first tier with at least selected other of the first-tier nodes (routing provided as peer to peer per col. 8 line 37 to col. 9 line 17) at least one of the first tier nodes forming a sink node (CH 3 per Fig 3 or sink node)

At least a second-tier mesh formed of a plurality of second tier nodes each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected other of the second-tier nodes with at least selected others of the second-tier nodes (CH1-CH4 in 32 per Fig 3 are second tier nodes in a mesh which are capable of communicating)

At least one of the second-tier nodes forming a second tier sink node the second-tier sink node further configured to communicate with the first-tier sink node of said first tier mesh (CH3 in 32 or second tier-sink node is capable of communicating with CH3 in 28 or first tier sink node per Fig 3)

Wherein the at least one of the first-tier node forming the first-tier sink node comprises a first first-tier node forming a first first-tier sink node and at least a second first tier node forming a second first-tier node (CH3 in 28 is a first first-tier node which is a sink and CH2 is a second first tier node which is a sink per Fig 3) wherein the at least one of the second-tier nodes forming the second-tier sink comprises a second-tier node forming a second-tier sink node (CH2 is the second second tier node), the first-tier sink node capable of communicating with the first second tier sink node (Tier nodes are capable of intercommunicating), the second first-tier sink node configured to communicate with the second second-tier sink node (tier nodes are capable of intercommunicating) and the first and second second-tier sink node respectively are capable of intercommunicating (tier nodes are capable of intercommunicating)

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar



of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

In addition Haas teaches:

Regarding claim 16, further comprising an other of the second-tier nodes of said second-tier mesh positioned between the first second-tier node sink node and a second second-tier sink node second-tier nodes effected by the way of the other second-tier nodes (There are other second-tier sink nodes in between per Fig 30

Referring to claim 17, the combination of Haas and Liu teaches the system of claim 15.

Haas does not expressly call for: wherein data communicated between the first-tier mesh is communicated at a first data rate wherein data communicated between the second tier nodes of said second tier mesh is communicated at a second data rate the second data rate greater than the first data rate such that data communicated between the first and second first-tier nodes is communicated more quickly by way of the first and second-tier sink nodes that by way of the first-tier mesh

Liu teaches: wherein data communicated between the first-tier mesh is communicated at a first data rate wherein data communicated between the second tier nodes of said second tier mesh is communicated at a second data rate the second data rate greater than the first data rate such that data communicated between the first and second first-tier nodes is communicated more quickly by way of the first and second-tier sink nodes that by way of the first-tier mesh (first frequency and second frequency in which high frequency rate is on backbone or second tier per Fig 1A col. 6 lines 45 to 54)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add the wherein data communicated between the first-tier mesh is communicated at a first data rate wherein data communicated between the second tier nodes of said second tier mesh is communicated at a second data rate the second data rate greater than the first data rate such that data communicated between the first and second first-tier nodes is communicated more quickly by way of the first and second-tier sink nodes that by way of the first-tier mesh of Liu to the first tier and second tier architecture network of the combination of Haas and Liu in order to improve performance by running a faster rate on the backbone than the first tier.

Referring to claim 20, Haas teaches: a method (Fig 3 performs the method) comprising forming a wireless access network providing for communication therein (Fig 3 is a wireless ad hoc network which forms in order to perform communication);

Forming a first-tier mesh of a plurality of first-tier nodes, each of the first-tier nodes capable of communicating data within the first tier with at least selected other of the first tier nodes (Fig 3 shows a first-tier mesh of a plurality of nodes which are a part of an ad-hoc network which forms and the nodes are capable of intercommunicating)

Forming a second-tier mesh of a plurality of second-tier nodes, each of the second tier nodes of the plurality of second-tier nodes capable of communicating data within the second tier with at least selected others of the second-tier nodes (Figure 3 shows an ad-hoc network which forms of second tier nodes with are capable of intercommunicating) at least one of the second tier nodes forming a second-tier sink node further capable of communicating with the first tier sink node of the first-tier mesh formed during said operation of forming the second-tier mesh (CH1-CH4 in 32 per Fig 3 are second tier nodes which are capable of communicating with CH1-CH4 which are their first tier counterparts)

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 22, Haas teaches: an apparatus (Fig 3) comprising: at least one first-tier node (nodes other than CH3 in 28 per Fig 3) wherein the at least one first-tier nodes form a first tier mesh (nodes other than CH3 in 28 per Fig 3 form a mesh), and the apparatus is configured to communicate data within the first tier with at least selected other of the at least one first-tier nodes (CH3 communicates with all of the node in 28 per Fig 3) and communicated data with a second tier sink node of a second-tier network (CH3 per 28 communicates with CH3 per 32 in Fig 3)

Wherein first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

In addition Haas teaches:

Regarding claim 6, wherein the first-tier nodes comprise mobile nodes configured to move through a selected area (First-tier nodes are ad-hoc mobile which are inherently capable of movement through a selected area)

Regarding claim 23, wherein the first-tier mesh comprises an ad-hoc mesh which exhibits an ad-hoc configuration and an ad-hoc number of the at least one of first-tier nodes (The first tier-mesh is an ad hoc network with an ad-hoc number of at least one first tier nodes per Fig 3)

Referring to claim 3, the combination of Haas and Liu teach: the apparatus of claim 22

Haas does not expressly call for: wherein the first tier-mesh operation characteristic comprise a first frequency band within which communication of data is effectuated wherein the second-tier mesh operational characteristics comprise second frequency bandwidth which communication of data is effectuated, the first frequency bandwidth and second frequency bandwidth having at least a plurality of nonoverlapping portions

Liu teaches: first tier mesh frequency bandwidth and second tier frequency bandwidth being within which communication of data is effectuated the first frequency bandwidth and the second frequency bandwidth having at least plurality of nonoverlapping portions (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to nonoverlapping frequency band of the first and second tier of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 24, Haas teaches: an apparatus (Figure 3) comprising: at least one second-tier node (CH 1 in 32 per Fig 3) wherein the at least one second-tier node is configured to form a second-tier mesh, and the apparatus is configured to communicate data within the second tier and at least selected other of the at least one second-tier node of a first-tier mesh(CH1-CH4 in 32 per Fig 3 are second tier nodes which are capable of communicating with CH1-CH4 which are their first tier counterparts)

wherein the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 25, Haas and Liu teaches: the apparatus of claim 24.

Haas does not expressly call for: wherein the second-tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes

Liu teaches: wherein the second-tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes (Fig 8)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add the second-tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes Liu in place of the ad hoc nodes of the combination of Haas and Liu in order to build a network which can utilize terrestrial interconnections and increase the bandwidth between second tier nodes.

Referring to claim 26, Haas teaches: a apparatus (Fig 3) comprising: at least one first-tier node ,where the at least one first tier nodes form a first-tier mesh (nodes other than CH3 in 28 are first tier nodes which form a mesh)

Means for communicating data within the first tier with at least selected other of at least one first-tier nodes (Fig 3 has nodes which have the capabilities of the nodes in Fig 1 which have transceiver per col. 6 lines 57 or means)

Means for communicating data with a second-tier sink node of a second -tier network (Fig 3 has nodes which have the capabilities of the nodes in Fig 1 which have transceiver per col. 6 lines 57 or means)

wherein the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 27, an apparatus (Fig 3) comprising: at least one second-tier node, where the at least one second tier nodes forms a second-tier mesh (node other than CH3 in 32 are second tier nodes which form a mesh)

Means for communicating data within the second tier with at least selected other of at least one second-tier node (Fig 3 has nodes which have the capabilities of the nodes in Fig 1 which have transceiver per col. 6 lines 57 or means)

Means for communicating data with a first-tier sink node of a first-tier mesh (Fig 3 has nodes which have the capabilities of the nodes in Fig 1 which have transceiver per col. 6 lines 57 or means) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar

of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 28, Haas teaches: a method (Fig 3 performs the method) comprising:

forming a first-tier mesh using at least one first-tier node (The ad-hoc network in Figure 3 has first tier node which form in a mesh) communicating data with the first tier node with at least selected other of the at least one first-tier nodes (All of the nodes in the first tier can intercommunicate)

Communicating data with a second-tier sink node of a second-tier network (The first tier nodes can communicate data CH 1 to CH 4 in 32 per Fig 3)

wherein the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

Referring to claim 30, the combination of Haas and Liu teach: the method of claim28

Haas does not expressly call for: wherein the first tier-mesh operation characteristic comprise a first frequency band within which communication of data is effectuated wherein the second-tier mesh operational characteristics comprise second frequency bandwidth which communication of data is effectuated, the first frequency bandwidth and second frequency bandwidth having at least a plurality of nonoverlapping portions

Liu teaches: first tier mesh frequency bandwidth and second tier frequency bandwidth being within which communication of data is effectuated the first frequency bandwidth and the second frequency bandwidth having at least plurality of nonoverlapping portions (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to nonoverlapping frequency band of the first and second tier of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

In addition Haas teaches:

Regarding claim 32, wherein the first-tier nodes comprise mobile nodes configured to move through a selected area (First-tier nodes are ad-hoc mobile which are inherently capable of movement through a selected area)

Referring to claim 29, Haas teaches a method (Fig 3 performs the method) comprising:

forming a second-tier mesh using at least one second-tier node (The ad-hoc network of Fig 3 forms the second-tier mesh)

communicating data within the second tier with at least selected other of the at least one second-tier node (CH1-CH4 in 32 can all intercommunicate)

and communicating data with a first-tier sink node of a first-tier mesh (CH1 –CH4 in 32 can communicate data with their respective counterpart in the tier-1 network per Fig 3)

wherein the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

3. Claims 4, 7, 10, 14, 31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Haas (U.S. Patent No.: 6,304,556) in view of Liu (U.S. Patent No.:6,980,537) further in view of Acampora (U.S. Patent No.: 6,751,455)

Referring to claim 4, Haas teaches the system of claim 1 and first tier nodes mesh and second tier nodes mesh and are configured to communicate.

Haas does not expressly call for: at least one first-tier node of said first-tier node and at least one second tier node of said second-tier mesh are co-located the at least one first-tier node co-located with the at least one second-tier node and at least the one second-tier node co-located with the at least first-tier

Acamora teaches: at least one first-tier node of said first-tier node and at least one second tier node of said second-tier mesh are co-located the at least one first-tier node co-located with the at least one second-tier node and at least the one second-tier node co-located with the at least first-tier (network in a home per col. 7 lines 61 or collocated)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add at least one first-tier node of said first-tier node and at least one second tier node of said second-tier mesh are co-located the at least one first-tier node co-located with the at least one second-tier node and at least the one second-tier node co-located with the at least first-tier of Acampora to the first tier and second tier of Haas in order to build a system in a home or business.

Referring to claim 7, the combination of Haas and Liu teaches: the apparatus of claim 5

The combination of Haas and Liu do not expressly call for: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique

Acampora teaches: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique (col. 2 lines 21 to 25)

It would have been obvious to add the short range radio capability of Acampora to the nodes of the combination of Haas and Liu in order to allow communication without line of sight restrictions.

Referring to claim 10, the combination of Haas and Liu teaches: the system of claim 9.

The combination of Haas and Liu do not expressly call for: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique

Acampora teaches: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique (col. 2 lines 21 to 25)

It would have been obvious to add the short range radio capability of Acampora to the nodes of the combination of Haas and Liu in order to allow communication without line of sight restrictions.



Referring to claim 14, the combination of Haas and Liu teaches: the system of claim 13.

The combination of Haas and Liu do not expressly call for: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique

Acampora teaches: wherein the communication data is effectuated pursuant to non line of sight (NOS) communication technique (col. 2 lines 21 to 25)

It would have been obvious to add the short range radio capability of Acampora to the nodes of the combination of Haas and Liu in order to allow communication without line of sight restrictions.

Referring to claim 31, the combination of Haas and Liu teach: the method of claim 28 and first tier nodes mesh and second tier nodes mesh and are configured to communicate.

Haas does not expressly call for: at least one first-tier node of said first-tier node and at least one second tier node of said second-tier mesh are co-located the at least one first-tier node co-located with the at least one second-tier node and at least the one second-tier node co-located with the at least first-tier

Acamora teaches: at least one first-tier node of said first-tier node and at least one second tier node of said second-tier mesh are co-located the at least one first-tier node co-located with the at least one second-tier node and at least the one second-tier node co-located with the at least first-tier (network in a home per col. 7 lines 61 or collocated)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add at least one first-tier node of said first-tier node and at least one second tier node of said second-tier mesh are co-located the at least one first-tier node co-located with the at least one second-tier node and at least the one second-tier node co-located with the at least first-tier of Acampora to the first tier and second tier of Haas in order to build a system in a home or business.

Referring to claim 33, the combination of Haas and Liu teaches: the method of claim 28

The combination of Haas and Liu do not expressly call for: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique

Acampora teaches: wherein the communication data is effectuated pursuant to non line of sight (NLOS) communication technique (col. 2 lines 21 to 25)

It would have been obvious to add the short range radio capability of Acampora to the nodes of the combination of Haas and Liu in order to allow communication without line of sight restrictions.

### ***Claim Objections***

4. Claims 1, 3-17, & 20-33 are objected to because of the following informalities: Referring to claims 1, 5, 8, 11, & 15; the examiner objects to the usage of "operable pursuant to" because "operable pursuant to" can be interpreted as an intended use and not a positive claim recitation. The examiner requests that the applicant clarify the meaning on the record. Appropriate correction is required. .  
Referring to claims 20, 22, 24, 26, 27, 28, & 29; the examiner objects to the usage of "operational pursuant to" because "operational pursuant to" can be interpreted as an intended use and not a positive claim recitation. The examiner requests that the applicant clarify the meaning on the record. Appropriate correction is required

### ***Response to Amendment***

5. Applicant's arguments with respect to claims 1, 3-17, & 20-33 have been considered but are moot in view of the new ground(s) of rejection.

The following is the examiner response relative to comments provided in response to the advisory action:

The examiner respectfully disagrees with the applicant's argument that the objection to words "operable pursuant to" or "operational pursuant to" which were in the advisory action has been traversed. The examiner objects to "operable pursuant to" and "operational pursuant to" because this wording could be interpreted as a non-positive claim recitation or an intended use. Applicant in their explanation failed to clarify if the meaning was a positive claim recitation.

The following is the examiner response relative to comments provided after final.

Referring to applicant's arguments on Pg 17 through 24 as an after final response. In general the applicant argument's repeat the whole claim language and say that the prior art references failed to teach all of the limitations. In order to be responsive and not totally repeat the whole rejection in this response one central argument appears through out this section which is that the combination of references in the independent claims 1, 5, 8, 11, 15, 20, 22, 24, 26-29 fail to teach or disclose: "the first tier nodes of said first-tier mesh are operable pursuant to a first-tier-mesh operational characteristics, and wherein the second-tier mesh are operational pursuant to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second tier mesh operational topological characteristic being different"

The examiner respectfully disagrees with the applicant argument that the combination of references fail to teach: "the first tier nodes of said first-tier mesh are operable pursuant to a first-tier-mesh operational characteristics, and wherein the second-tier mesh are operational pursuant

to second-tier-mesh operation characteristics, a first-tier-mesh operational topological characteristics and a second tier mesh operational topological characteristic being different”

Haas teaches: the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operable pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

The examiner respectfully disagrees with the applicant's argument that Haas does not teach "at least one first-tier node forming a first-tier sink node and at least one of the second tier nodes forming a second-tier sink node the second-tier sink node further configured to communicate data with the first-tier sink node of said first-tier mesh”

The applicant broadly claims a "first-tier sink node" and a "second tier sink node".

Haas teaches: at least one first-tier node forming a first-tier sink node and at least one of the second tier nodes forming a second-tier sink node the second-tier sink node further configured to communicate data with the first-tier sink node of said first-tier mesh (Routes between all nodes in the first tier and second tier nodes one of which the examiner interprets as a first tier sink node and another node which the examiner interprets as a second tier sink node per col. 8 lines 21 to 67)

The applicant has broadly claimed operational characteristic and second tier operation characteristics being dissimilar

The examiner respectfully disagrees with the applicant's argument that the combination of references Liu and Haas failed to disclosed “operational characteristic and second tier operation characteristics being dissimilar” because Liu teaches using different frequencies as the sole functional difference between the operating conditions of the different mesh networks

The Liu teaches using different frequencies as the sole functional difference between the operation conditions of the differ mesh networks per col. 6 lines 49-58.

The applicant has failed to provide a persuasive argument as to why using different frequencies on different tiers does not read on operational characteristics and second tier operation characteristics being dissimilar.

The examiner respectfully disagrees with the applicant's argument that the combination of reference fail to teach: wherein said second-tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes

Haas teaches: wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Hass does not expressly call for: wherein said second tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes or first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: wherein said second tier mesh comprises a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes (col. 14 lines 27 to 61) and first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add a pre-configured mesh which exhibits a fixed configuration and a fixed number of second-tier nodes and first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

The examiner respectfully disagrees with the applicant's argument that because Liu teaches a dynamic network that this is teaching away from a preconfigured mesh. Preconfigured mesh deals with an initial condition and after that initial condition the system can dynamically change.

The examiner respectfully disagrees with the applicant's argument that the combination of references do not expressly call for: "third tier mesh formed of a plurality of third-tier nodes each of the third-tier nodes of the plurality of third-tier nodes configured to communicated data with at least selected other of the third tiers nodes at least one of the third-tier nodes forming a third-tier sink node

Haas teaches: At least a second-tier mesh formed of a plurality of second tier nodes each of the second-tier nodes of the plurality of second-tier nodes configured to communicate data within the second tier with at least selected other of the second-tier nodes (CH1-CH4 in 32 per Fig 3 are second tier nodes in a mesh which are capable of communicating) the second-tier sink node further capable of communicating with the first-tier sink node of said first-tier sink mesh (CH3 in 32 or second tier-sink node is capable of communicating with CH3 in 28 or first tier sink node per Fig 3)

Wherein the system is configured to provide radio communication of data therein (Nodes in Figure 3 are mobile nodes so wireless access is provided) and the first-tier nodes of the first-tier mesh are operable pursuant to a first tier-mesh operational characteristic and wherein the second-tier nodes of said second-tier mesh are operational pursuant to a second-tier mesh operation characteristics (The first tier nodes are operable pursuant a first tier-mesh operational characteristic of being a node whereas the second tier are operable pursuant to a second-tier mesh operation of being cluster heads per col. 8 lines 37 to 65)

Haas does not expressly call for: a third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes capable of communicating data with at least selected other of the third tier nodes, at least one of the third-tier nodes forming a third tier sink node and first tier mesh operational characteristic and second tier operation characteristics being dissimilar.

Liu teaches: a third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes capable of communicating data with at least selected other of the third tier nodes (col. 5 lines 39 to 53 and per col. 14 lines 29 to 61 and per Fig 8) at least one of the third-tier nodes forming a third tier sink node (super node is a third tier sink node col. 5 lines 39 to 53 and per col. 14 lines 29 to 61 and per Fig 8) and first tier mesh operational characteristic and second tier operation characteristics being dissimilar (tiers utilize different frequencies per col. 6 lines 41 to 62)

It would have been obvious to one of ordinary skill in the art at the time of the invention to add third-tier mesh formed of a plurality of third-tier nodes, each of the third-tier nodes of the plurality of third-tier nodes capable of communicating data with at least selected other of the third tier nodes, at least one of the third-tier nodes forming a third tier sink node and first tier mesh operational characteristic and second tier operation characteristics being dissimilar of Liu to the first tier and second tier of Haas in order to build a system in communications does not interfere.

The examiner finds applicant's argument's unpersuasive.

***Conclusion***

6. Any inquiry concerning this communication or earlier communications from the examiner should be directed to ROBERT W. WILSON whose telephone number is (571)272-3075. The examiner can normally be reached on M-F (8:00-4:30).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jay Patel can be reached on 571/272-2988. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Robert W Wilson/  
Primary Examiner, Art Unit 2419

RWW